

Sullivan **Palatek®**

“The Ultimate Performance Rotary Screw Air Compressor”



ENCLOSED CDD
MODEL SHOWN



EXTENDED LIFE
*Mounted desiccant dryer
to eliminate moisture
and contaminants,
-40° F Dew Point.*

- Rotary screw compressor,
cool, clean air.
- Compact design.
- 100 percent duty cycle.
- 5-year air end warranty.

*Complete package with starter,
air cooled oil cooler/aftercooler
and protective devices for high
temperature and low oil shutdown.
In line filter.*

COMPRESSOR & DESICCANT DRYER PACKAGE

STANDARD FEATURES

ELECTRIC MOTOR:	Nema T-Frame, C-Frame, double shaft, open drip proof squirrel cage, induction type. Contact factory for voltage availability. Direct coupling to motor for positive alignment.
MOTOR STARTER:	Full voltage magnetic starter with 120 volt controls, Nema 1 enclosure, circuit breaker, transformer and three phase overload protector.
AIR INTAKE FILTER:	Multi-stage dry type with replaceable element.
CONTROLS:	Full modulation, electronically controlled for smooth operation and lowest possible no load power. Auto dull control, timed stop or constant run.
INSTRUMENTATION:	Line press gauge, fluid reservoir gauge, hour meter, discharge temperature gauge, oil filter and separator element differential gauges.
PROTECTIVE DEVICES:	Class 20 overload relay, high temperature and overpressure shut down.
COOLING SYSTEM:	Air cooled with air cooler/aftercooler and factory filled with Palasyn 45 synthetic lubricoolant. Equipped with microfiber full flow oil filter.
AIR DRYER:	Desiccant air dryer and coalescing air filter for moisture removal, spin on replaceable cartridges and built for -40°F dew point.
MOUNTING:	Base mounted, no special foundation required. Optional tank, platform and accoustical enclosure available. Consult factory for dimensions and weights for optional equipment.

GENERAL SPECIFICATIONS

MODEL	BASE PACKAGE	ENCLOSED PACKAGE
Lubricant Reservoir Capacity	3 Gal.	3 Gal.
Length	58"	77"
Height	35"	43"
Width	34"	38"
Weight (lbs.)	1,050	1,650
Discharge Connection	1"N.P.T.	1"N.P.T.

Sold and Serviced By:**CDD 15-30 HP****TANK MOUNTED OPEN CDD MODEL SHOWN.**