

Sullivan Palatek.

“ The Ultimate Performance Rotary Screw Air Compressor ”



EXTENDED LIFE
*Mounted desiccant dryer
to eliminate moisture
and contaminants,
-40° F Dew Point.*

**STANDARD CDD
MODEL SHOWN**



- Rotary screw compressor,
cool, clean air.
- Compact design.
- 100 percent duty cycle.
- 2-year air end warranty.

*Complete package with starter,
air cooled oil cooler/aftercooler
and protective devices for high
temperature and low
oil shutdown.*

COMPRESSOR & DESICCANT DRYER PACKAGE

STANDARD FEATURES

COMPRESSOR:	Oil flooded rotary screw, continuous duty, industrial air compressor.
ELECTRIC MOTOR:	200/208/230/460/575 VOLT, 3-phase, open drip motor. Single phase 230 volt, 5, & 7.5 HP also available.
MOTOR STARTER:	Full voltage magnetic starter with 110 volt control.
CONTROLS:	Constant speed with two operating modes, continuous run or auto start/stop.
INSTRUMENTATION:	Line pressure gauge, operating temperature gauge, hour meter.
COOLING SYSTEM:	Air cooled oil cooler/aftercooler with Palasyn 45 (4000 hour) synthetic lubricoolant. Spin on type lube filter and air/oil separator for ease of maintenance.
AIR FILTER:	Replaceable dry type.
AIR DRYER:	Desiccant Air Dryer/Filter for moisture removal. Spin on replaceable cartridges with desiccant contained filter media enclosure. - 40°F Dew Point.
AIR RECEIVER:	80 gal. with auto-drain, relief valve and pressure gauge. Other size receivers available.

GENERAL SPECIFICATIONS

MODEL	CDD	CDDE
Oil Reservoir Capacity	1 Gal.	1 Gal.
Length	69"	69"
Height	54"	60"
Width	26-1/4"	33"
Weight (lbs.) 5HP	700	775
Weight (lbs.) 7.5 HP	750	825
Weight (lbs.) 10HP	800	875
Discharge Connection	1/2"N.P.T.	1/2"N.P.T.

Sold and Serviced By:

OPTIONAL CDDE MODEL SHOWN