

MODEL 5, 7.5, 10 HP

Sullivan **Palatek®**

“The Ultimate Performance Rotary Screw Air Compressor”



STANDARD CDF MODEL SHOWN.

- Rotary screw compressor, cool, clean air.
- Compact design.
- 100 percent duty cycle.
- 2-year air end warranty.

Complete package with starter, air cooled oil cooler/aftercooler and protective devices for high temperature and low oil shut-down.

Mounted air dryer and filter to eliminate moisture and contaminants.

COMPRESSOR, DRYER & FILTER PACKAGE

STANDARD FEATURES

COMPRESSOR:	Oil flooded rotary screw, continuous duty, industrial air compressor.
ELECTRIC MOTOR:	200/208/230/460/575 VOLT, 3-phase, open drip motor. Single phase 230 volt, 5, & 7.5 HP also available.
MOTOR STARTER:	Full voltage magnetic starter with 110 volt control.
CONTROLS:	Constant speed with two operating modes, continuous run or auto start/stop.
INSTRUMENTATION:	Line pressure gauge, operating temperature gauge, hour meter.
COOLING SYSTEM:	Air cooled oil cooler/aftercooler with Palasyn 45 (4000 hour) synthetic lubricoolant. Spin on type lube filter and air/oil separator for ease of maintenance.
AIR FILTER:	Replaceable dry type.
AIR DRYER:	SPRF: 23, 29, or 47CFM Air Dryer for moisture removal.
AIRLINE FILTER:	Mounted for contaminant removal.
AIR RECEIVER:	120 gal. with auto-drain, relief valve and pressure gauge.

GENERAL SPECIFICATIONS

MODEL	CDF
Oil Reservoir Capacity	1 Gal.
Length	72"
Height	61"
Width	26-1/4"
Weight (lbs.) 5HP	795
Weight (lbs.) 7.5 HP	845
Weight (lbs.) 10HP	900
Discharge Connection	1/2"N.P.T.

Sold and Serviced By: