

Sullivan Palatek®

M5, M7.5, M10HP

“The Ultimate Performance Rotary Screw Air Compressor”



Unit comes complete with starter, air cooled oil cooler/aftercooler, protective devices for high temperature and motor overload.

- Compact Design ● New Profile Design

STANDARD FEATURES

MODEL M5, M7.5 M10HP

COMPRESSOR

Modular oil flooded rotary screw,
continuous duty, industrial air compressor

ELECTRIC MOTOR

208/230/460/575 volt, 3-phase, open drip
motor. Single phase 230 volt available on all models.

MOTOR STARTER

Full voltage magnetic starter with 110 volt
control power.

CONTROLS

Automatic control (dual control) is standard

INSTRUMENTATION

Line pressure gauge, oil temperature
gauge and hour meter.

COOLING SYSTEM

Air cooled oil cooler/aftercooler with
Palasyn 45, 4000 hour synthetic oil, spin
on type oil filter and separator elements for
ease of maintenance.

AIR FILTER

Combination pleated and foam dry type,
easily replaceable.

OPTIONS

Moisture separator trap, platform mounted,
air receiver mounted (80, 120, 200 gallon).
Consult factory for accessories not listed.
Specifications subject to change without notice.

GENERAL SPECIFICATIONS

Oil Reservoir Capacity	1 Gal.
Length	38 5/8"
Height	26"
Width	24"
Weight E5HP	210 Lbs
Weight E7.5HP	280 Lbs
Weight E10HP	330 Lbs

Sold and Serviced by:

